

**AUTOTRANSFORMADORES  
MONOFASICOS REVERSIBLES**
**100 - 4000VA**
**Clase I**
**125 - 220V / 50 - 60 Hz**

TIPO	CARACTERISTICAS ELECTRICAS				CARACTERISTICAS FISICAS				
	Potencia ( VA )	V / Hz	Intensidad 125V ( A )	Intensidad 220V ( A )	DIMENSIONES			Peso ( grs.)	Unidades Embalaje
					A ( mm )	B ( mm )	C ( mm )		
ATR 10/12-22	100	125/220 / 50-60	0,8	0,45	75	62	102	1000	12
ATR 20/12-22	200	125/220 / 50-60	1,6	0,9	84	70	125	1800	10
ATR 30/12-22	300	125/220 / 50-60	2,4	1,35	84	70	125	1800	10
ATR 40/12-22	400	125/220 / 50-60	3,2	1,8	96	80	125	2320	10
ATR 50/12-22	500	125/220 / 50-60	4	2,25	96	80	130	2570	10
ATR 75/12-22	750	125/220 / 50-60	6	3,4	108	90	145	3930	8
ATR 100/12-22	1000	125/220 / 50-60	8	4,5	126	105	152	5150	4
ATR 150/12-22	1500	125/220 / 50-60	12	6,8	126	105	174	6750	2
ATR 200/12-22	2000	125/220 / 50-60	16	9	126	105	195	8500	2
ATR 250/12-22	2500	125/220 / 50-60	20	11,25	150	125	198	11000	2
ATR 300/12-22	3000	125/220 / 50-60	24	13,5	150	125	215	13250	2
ATR 400/12-22	4000	125/220 / 50-60	32	18	150	125	215	15000	2

110-230V bajo demanda.

