

**INDEPENDENT CONTROL GEAR UNITS
ENCAPSULATED. HIGH POWER FACTOR
FOR MERCURY VAPOUR LAMPS**

80 - 400W

**Built-in Capacitor
Indoor and built-in use**

230V / 50 Hz

Terminal type 1 \square 1 - 2,5 mm²

VDE 0712 EN 61347-60923 tw 130 **CLASE II**  **IP 20**

MODEL	TYPE	CONTROL GEAR UNITS								PHYSICAL CHARACTERISTICS					
		LAMP		V/Hz	I	Mains Current (A)	T ^a amb.	Diagrams	IP	DIMENSIONS				Weight (grs.)	Packing Units
		Wattage (W)	Current (A)							A (mm)	B (mm)	C (mm)	D (mm)		
HEC AF 8/23-F		80	0,80	230/50	0,95	0,42	50	18	20	155,5	141	74,2	64,7	1250	6
HEC AF 12/23-F		125	1,15	230/50	0,95	0,64	50	18	20	169,5	155	74,2	64,7	1600	6
HEC AF 25/23-F		250	2,15	230/50	0,95	1,24	50	18	20	178	162	97,2	86	2825	4
HEC AF 40/23-F		400	3,25	230/50	0,95	1,85	50	18	20	198	182	97,2	86	3725	4

Other voltages and frequencies are available on request

IP 20

