


**INDEPENDENT CONTROL GEAR UNITS
ENCAPSULATED. HIGH POWER FACTOR
FOR MERCURY VAPOUR LAMPS**

80 - 400W

**Built-in Capacitor
Outdoor, indoor and built-in use**

230V / 50 Hz

VDE 0712 EN 61347-60923 tw 130 **CLASE II**  **IP 65**

MODEL	TYPE	CONTROL GEAR UNITS								PHYSICAL CHARACTERISTICS				Packing Units	
		LAMP		V/Hz	I	Mains Current (A)	T ^a amb.	Diagrams	IP	DIMENSIONS					Weight (grs.)
		Wattage (W)	Current (A)							A (mm)	B (mm)	C (mm)	D (mm)		
HEC AF 8/23-M		80	0,80	230/50	0,95	0,42	50	19	65	155,5	141	74,2	64,7	1250	6
HEC AF 12/23-M		125	1,15	230/50	0,95	0,64	50	19	65	169,5	155	74,2	64,7	1600	6
HEC AF 25/23-M		250	2,15	230/50	0,95	1,24	50	19	65	178	162	97,2	86	2825	4
HEC AF 40/23-M		400	3,25	230/50	0,95	1,85	50	19	65	198	182	97,2	86	3725	4

Other voltages and frequencies are available on request
Separated input/output cables on request

IP 65

