



**TRANSFORMERS FOR LOW VOLTAGE
HALOGEN LAMPS 12V / 50-105VA**
Primary Voltage: 230V / 50-60Hz
Secondary Voltage: 11,5V

Standard Cross-Section **37 x 41**

(A) With thermal protection

EN 61558

TYPE	PRIMARY			SECONDARY			Diagrams	APPROVALS			PHYSICAL CHARACTERISTICS				
	Voltage (V)	Wattage (VA)	Fuse "T" (A)	Voltage (V)	Current (A)	Fuse "TL" (A)		01	01	DIMENSIONS				Weight (grs.)	Packing Units
										A (mm)	B (mm)	C (mm)	D (mm)		
TRI -50 REC	230	50	4	11,5	4	4	29	*	*	175	162	40,5	37	1000	20
TRI-50 REC-PTC (A)	230	50	-	11,5	4	4	30	*	*	175	162	40,5	37	1000	20
TRI -50 C	230	50	4	11,5	3,9	4	29	*	*	150	138	40,5	37	840	20
TRI-50 C-PTC (A)	230	50	-	11,5	3,9	4	30	*	*	150	138	40,5	37	840	20
TRI-60 C	230	60	-	11,5	4,75	5	29			150	138	40,5	37	840	20
TRI-60 C-PTC (A)	230	60	-	11,5	4,75	5	30			150	138	40,5	37	840	20
TRI-105 REC	230	105	0,5	12	8,15	-	30			245	235	41	28,5	1400	14
* TRI-105 REC-P (A)	230	105	-	12	7,65	-	32			245	235	41	28,5	1400	14

Other voltages available on request



According to EN 60598

