

**ENCAPSULATED TRANSFORMERS
FOR LOW VOLTAGE HALOGEN
LAMPS 12V / 50-60VA**

Primary Voltage: 230V / 50-60Hz

Secondary Voltage: 11,5V

Standard Cross-Section **42 x 46**

Class II

(A) With thermal protection

EN 61558

TYPE	PRIMARY		SECONDARY			Diagrams	APPROVALS		PHYSICAL CHARACTERISTICS					
	Voltage (V)	Wattage (VA)	Voltage (V)	Current (A)	Fuse "TL" (A)		DIMENSIONS				Weight (grs.)	Packing Units		
							A (mm)	B (mm)	C (mm)	D (mm)				
TRI-50 ENC	230	50	11,5	3,9	4	31			180	169	46	42	1020	20
TRI-50 ENC-PTC (A)	230	50	11,5	3,9	-	31			180	169	46	42	1020	20
TRI-50 ENC-C	230	50	11,5	3,9	4	29			180	169	46	42	1020	20
TRI-50 ENC-C PTC (A)	230	50	11,5	3,9	-	31			180	169	46	42	900	20
TRI-60 ENC-C	230	60	11,5	4,75	5	29			180	169	46	42	1020	20
TRI-60 ENC-C PTC (A)	230	60	11,5	4,75	-	31			180	169	46	42	1020	20

Other voltages available on request

