

**REVERSIBLE THREE-PHASE  
AUTOTRANSFORMERS**
**2 - 25 KVA**

Class I

**220 - 380V / 50 - 60 Hz**

TYPE	ELECTRICAL CHARACTERISTICS				PHYSICAL CHARACTERISTICS				
	Wattage ( VA )	V / Hz	Current 220V ( A )	Current 380V ( A )	DIMENSIONS			Weight ( grs. )	Packing Units
					A ( mm )	B ( mm )	C ( mm )		
ATR / 2	2000	220/380 / 50-60	5,26	3	320	240	310	14000	1
ATR / 3	3000	220/380 / 50-60	7,89	4,54	320	240	310	17000	1
ATR / 5	5000	220/380 / 50-60	13,15	7,57	320	240	310	21000	1
ATR / 8	8000	220/380 / 50-60	21,05	12,12	350	280	360	30000	1
ATR / 10	10000	220/380 / 50-60	26,30	15,15	350	280	360	40000	1
ATR / 15	15000	220/380 / 50-60	39,47	22,72	460	300	410	57000	1
ATR / 20	20000	220/380 / 50-60	52,63	30,30	530	370	540	80000	1
ATR / 25	25000	220/380 / 50-60	65,78	37,87	530	370	540	92000	1

**THREE-PHASE HP-KVA CONVERSION TABLE**

HP	KVA	HP	KVA
0,75	0,55	7,5	5,5
1	0,75	10	7,5
1,5	1,10	13,5	10
2	1,50	15	11
3	2,20	20	15
4	3	25	18,5
5,5	4	30	22

